

**ARDINAL** SAFETY DATA SHEET

# T241-GR11 PLATINUM GRAY

## **1. PRODUCT AND COMPANY IDENTIFICATION**

PRODUCT NAME:	T241-GR11 PLATINUM GRAY
PRODUCT USE:	Industrial Powder Coating

## MANUFACTURER

Cardinal Paint and Powder 1329 Potrero Ave S. El Monte, CA, 91733 626 444-9274

## 24 HR. EMERGENCY TELEPHONE NUMBER

CHEMTREC (US Transportation): (800)424-9300 CHEMTREC (International Transportation): (202)483-7616 WEB: WWW.CARDINALPAINT.COM

### 2. HAZARDS IDENTIFICATION

#### **PICTOGRAMS**:



#### SIGNAL WORD : DANGER

## HAZARD STATEMENTS :

- H412 Harmful to aquatic life with long lasting effects.
- H340 May cause genetic defects.
- H351 Suspected of causing cancer.
- H317 May cause an allergic skin reaction.
- H372 Causes damage to organs through prolonged or repeated exposure.
- H318 Causes serious eye damage.

#### **PRECAUTIONARY STATEMENTS :**

- P201 Obtain special instructions before use.
- P260 Do not breathe dust.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P202 Do not handle until all safety precautions have been read and understood.

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	Weight %	CAS Number	
Titanium Dioxide	15% - 20%	13463-67-7	
1,3,5-Triglycidyl Isocyanurate	1% - 5%	2451-62-9	
Hydrated magnesium silicate	1% - 5%	14807-96-6	
Aluminum Oxide	<1%	1344-28-1	
Crystalline Silica	0.10% - 0.50%	14808-60-7	



## 4. FIRST AID MEASURES

#### Description of first aid measures.

**EYE CONTACT :** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center or doctor/physician.

**SKIN CONTACT**: Remove affected clothing and wash all exposed area with mild soap and water, followed by warm water rinse. Wash with plenty of soap and water. If skin irritation or rash occurs: Wash with plenty of soap and water. Get medical advice/attention. Wash contaminated clothing before reuse. Brush off loose particles from skin. Immerse in cool water/wrap in wet bandages.

**INGESTION :** Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention. Call a Poison Center or doctor/physician if you feel unwell

**INHALATION :** Allow Victim to breathe fresh air. Allow victim to rest. Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a Poison Center or doctor/physician if you feel unwell

**Most important symptoms and effect, both acute and delayed :** Symptoms/Injuries: May cause genetic defects. Causes damage to organs. - After Inhalation: Danger of serious damage to health by prolonged exposure through inhalation. Harmful if inhaled. May cause an allergic skin reaction. May cause cancer by inhalation. - After Eye Contact: Causes serious eye damage. - After Ingestion: Swallowing a small quantity of this material may result in serious health hazard. Indication of any immediate medical attention and special treatment needed: No additional information available.

### **5. FIRE FIGHTING MEASURES**

SUITABLE EXTINGUISHING MEDIA: Foam, alcohol foam, dry chemical, carbon dioxide, water fog or sand.

**UNSUITABLE EXTINGUISHING MEDIA:** Do not use heavy water stream.

**FIRE FIGHTING PROCEDURE:** Firefighting instructions: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering the environment.

Protection during firefighting: Firefighters should wear full protective gear. Do not enter fire area without proper protective equipment, including self-contained breathing apparatus with full face piece operated in pressure demand or other positive pressure modes.

UNUSUAL FIRE AND EXPLOSION HAZARD: This product is stable at normal handling and storage conditions.

## 6. ACCIDENTAL RELEASE MEASURES

**PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES :** General measures: Remove ignition sources. Use special care to avoid static electric charges. No smoking.

FOR NON-EMERGENCY PERSONNEL : For non-Emergency procedures: Evacuate unnecessary personnel.

**FOR EMERGENCY RESPONDERS :** Protective equipment : Equip cleanup crew with proper protection. - Emergency procedures : Ventilate area.

**ENVIRONMENTAL PRECAUTIONS :** Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public water. Avoid release to the environment.

**METHODS AND MATERIAL FOR CONTAINMENT AND CLEAN UP :** On land, sweep or shovel into suitable containers,. Minimize generation of dust.

## 7. HANDLING AND STORAGE

**PRECAUTIONS FOR SAFE HANDLING :** Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when you are leaving work. Provide good ventilation in process area.Use only in well ventilated areas. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood.Eliminate all ignition sources if safe to do so. Avoid breathing dust, fumes and/or vapors.

Hygiene measures: Wash Skin thoroughly after handling.



**CONDITIONS FOR SAFE STORAGE, INCLUDING INCOMPATIBILITIES :** Avoid heat sources and direct sunlight. Store in a dry place. Protect from moisture. Keep container closed when not in use. Keep only in the original container in a cool well ventilated place away from heat, ignition sources and direct sunlight.

Incompatible products: Strong bases. Strong acids.

Incompatible materials: Source of ignition. Direct sunlight.

## 8. EXPOSURE CONTROLS\PERSONAL PROTECTION

ACGIH TLV (Threshold Limit Value) 2-Mercaptobenzothiazole(149-30-4) USA WEEL (WEEL) TWA Aluminum Oxide(1344-28-1) USA OSHA USA OSHA (OEL) Table Z-1, TWA (DEL) Table Z-1, TWA (DEL) Table Z-1, TWA (DEL) Table Z-1, TWA (DEL) Table Z-3) USA NIOSH Amorphous Pyrogenic Silica(112945-52-5) USA NIOSH USA OSHA USA NIOSH USA NIOSH USA NIOSH Carbon Black(1333-86-4) ACGIH TLV (Threshold Limit Value) ITWA (Time Weighted Average) J.S mg/m3 & hours TWA (Time Weighted Average) J.S mg/m3 & hours NIOSH REL (Recommended Exposure Limit) NIOSH REL (Recommende Exposu	1,3,5-Triglycidyl Isocyanurate(2451-62-9)			
2-Mercaptobenzothiazole(149-30-4)       (WEEL) TWA       5 mg/m3         USA WEEL       (WEEL) TWA       15 mg/m3         Aluminum Oxide(1344-28-1)       USA OSHA       10 mg/m3         USA ACGIH       (TLV) TWA       1 mg/m3         Amorphous Pyrogenic Silica(112945-52-5)       80 mg/m3 3/%SiO2         USA NOSH       USA OSHA       6 mg/m3         Morphous Silica(112926-00-8)       0SA OSHA TWA (REL)       6 mg/m3         USA OSHA       USA OSHA TWA (Table Z-1)       6 mg/m3         Carbon Black(133-86-4)       USA OSHA TWA (Table Z-3)       20 Million particals per cubic foot.         Carbon Black(133-86-4)       TWA (Time Weighted Average)       3. mg/m3 8 hours         NIOSH REL (Recommended Exposure Limit)       TWA (Time Weighted Average)       3.5 mg/m3 8 hours         NIOSH REL (Recommended Exposure Limit)       TWA (Time Weighted Average)       0.1mg of PAHs/cm3 10 hours         NIOSH REL (Recommended Exposure Limit)       TWA (Time Weighted Average)       0.25 mg/m3 8 hours         NIOSH REL (Recommended Exposure Limit)       TWA (Time Weighted Average)       0.2025 mg/m3 8 hours         NIOSH REL (Recommended Exposure Limit)       TWA (Time Weighted Average)       2 mg/m3 (Respirable Fraction) 8 hours         NIOSH REL (Recommende Exposure Limit)       TWA (Time Weighted Average)       2 mg/m3 (Respirable Fraction	ACGIH TLV (Threshold Limit Value)	TWA (Time Weighted Average)	0.05 mg/m3 8 hours	
Aluminum Oxide(1344-28-1)       10 mg/m3         USA ACGIH       (DEL) Table Z-1, TWA       15 mg/m3         USA ACGIH       (TLV) TWA       1 mg/m3         Amorphous Pyrogenic Silica(112945-52-5)       USA OSHA       USA OSHA         USA NIOSH       USA OSHA       6 mg/m3         Amorphous Silica(112926-00-8)       USA OSHA       6 mg/m3         USA OSHA       USA OSHA TWA (Table Z-1)       6 mg/m3         USA OSHA       USA OSHA TWA (Table Z-1)       6 mg/m3         USA OSHA       USA OSHA TWA (Table Z-3)       20 Million particals per cubic foot.         USA NIOSH       USA OSHA       USA OSHA TWA (Table Z-3)       20 Million particals per cubic foot.         USA OSHA       USA OSHA TWA (Table Z-3)       20 Million particals per cubic foot.       Carbon Black(1333-86-4)         ACGIH TLV (Threshold Limit Value)       TWA (Time Weighted Average)       3.5 mg/m3 & hours       NIOSH REL (Recommended Exposure         Limit)       TWA (Time Weighted Average)       0.1mg of PAHs/cm3 10 hours       NIOSH REL (Recommended Exposure       TWA (Time Weighted Average)       0.025 mg/m3 & hours         Hydrated magnesium silicate(14807-96-6)       TWA (Time Weighted Average)       2 mg/m3 (Respirable Fraction) 8 hours         NIOSH REL (Recommended Exposure       TWA (Time Weighted Average)       2 mg/m3 (Respirable Fraction	2-Mercaptobenzothiazole(149-30-4)			
USA(OEL) Table Z-1, TWA15 mg/m3USA ACGIH(TLV) TWA1 mg/m3Amorphous Pyrogenic Silica(112945-52-5)80 mg/m3 3/%SiO2USA NIOSHUSA OSHAUSA OSHA TWA (OEL Table Z-3)80 mg/m3 3/%SiO2USA NIOSHUSA NIOSH TWA (REL)6 mg/m3Amorphous Silica(112926-00-8)56 mg/m3USA OSHAUSA OSHA TWA (Table Z-1)6 mg/m3USA OSHAUSA OSHA TWA (Tabla Z-3)20 Million particals per cubic foot.USA NIOSHUSA NIOSH TWA (REL)6 mg/m3Carbon Black(1333-86-4)TWA (Time Weighted Average)3.5 mg/m3 8 hoursACGIH TLV (Threshold Limit Value)TWA (Time Weighted Average)3.5 mg/m3 8 hoursNIOSH REL (Recommended ExposureTWA (Time Weighted Average)0.1mg of PAHs/cm3 10 hoursLimit)TWA (Time Weighted Average)0.025 mg/m3 8 hoursCrystalline Silica(14808-60-7)TWA (Time Weighted Average)2 mg/m3 (Respirable Fraction) 8 hoursNIOSH REL (Recommended ExposureTWA (Time Weighted Average)2 mg/m3 (Respirable Fraction) 10 hoursLimit)TWA (Time Weighted Average)2 mg/m3 (Respirable Fraction) 10 hoursNIOSH REL (Recommended ExposureTWA (Time Weighted Average)2 mg/m3 (Respirable Fraction) 10 hoursNIOSH REL (Recommended ExposureTWA (Time Weighted Average)2 mg/m3 (Respirable Fraction) 10 hoursNIOSH REL (Recommende ExposureTWA (Time Weighted Average)15 mg/m3 (Total Dust) 8 hoursNIOSH REL (Permissible Exposure Limit)TWA (Time Weighted Average)15 mg/m3 (Total Dust) 8 hours <td>USA WEEL</td> <td>(WEEL) TWA</td> <td>5 mg/m3</td>	USA WEEL	(WEEL) TWA	5 mg/m3	
USA ACGIH(TLV) TWA1 mg/m3Amorphous Pyrogenic Silica(112945-52-5)USA OSHAUSA OSHA TWA (OEL Table Z-3)80 mg/m3 3/%SiO2USA NIOSHUSA NIOSH TWA (REL)6 mg/m3Amorphous Silica(112926-00-8)USA OSHA TWA (Table Z-1)6 mg/m3USA OSHAUSA OSHA TWA (Table Z-3)20 Million particals per cubic foot.USA OSHAUSA OSHA TWA (Table Z-3)20 Million particals per cubic foot.USA OSHAUSA OSHA TWA (Table Z-3)20 Million particals per cubic foot.USA NIOSHUSA NIOSH TWA (REL)6 mg/m3Carbon Black(1333-86-4)TWA (Time Weighted Average)3.5 mg/m3 8 hoursACGIH TLV (Threshold Limit Value)TWA (Time Weighted Average)3.5 mg/m3 8 hoursOSHA PEL (Permissible Exposure Limit)TWA (Time Weighted Average)3.5 mg/m3 8 hoursNIOSH REL (Recommended ExposureTWA (Time Weighted Average)0.1mg of PAHs/cm3 10 hoursLimit)TWA (Time Weighted Average)0.025 mg/m3 8 hoursNIOSH REL (Recommended ExposureTWA (Time Weighted Average)2 mg/m3 (Respirable Fraction) 8 hoursHydrated magnesium silicate(14807-96-6)TWA (Time Weighted Average)2 mg/m3 (Respirable Fraction) 10 hoursACGIH TLV (Threshold Limit Value)TWA (Time Weighted Average)2 mg/m3 (Respirable Fraction) 10 hoursNIOSH REL (Recommende ExposureTWA (Time Weighted Average)15 mg/m3 (Respirable Fraction) 10 hoursLimestone(1317-65-3)ACGIH TLV (Threshold Limit Value)TWA (Time Weighted Average)15 mg/m3 (Respirable Fraction) 8 hoursNIOSH REL (Recommende ExposureTWA	Aluminum Oxide(1344-28-1)			
Amorphous Pyrogenic Silica(112945-52-5)       USA OSHA TWA (OEL Table Z-3)       80 mg/m3 3/%SiO2         USA NIOSH       USA NIOSH WA (REL)       6 mg/m3         Amorphous Silica(112926-00-8)       USA OSHA       USA OSHA TWA (Table Z-1)       6 mg/m3         USA NIOSH       USA OSHA TWA (Table Z-1)       6 mg/m3         USA OSHA       USA OSHA TWA (Table Z-1)       6 mg/m3         Carbon Black(1333-86-4)       ACGIH TLV (Threshold Limit Value)       TWA (Time Weighted Average)       3.5 mg/m3 8 hours         OSHA PEL (Permissible Exposure Limit)       TWA (Time Weighted Average)       3.5 mg/m3 8 hours       0.1mg of PAHs/cm3 10 hours         NIOSH REL (Recommended Exposure       TWA (Time Weighted Average)       0.1mg of PAHs/cm3 10 hours       0.1mg of PAHs/cm3 10 hours         Limit)       TWA (Time Weighted Average)       0.25 mg/m3 8 hours       0.025 mg/m3 8 hours         Hydrated magnesium silicate(14807-96-6)       TWA (Time Weighted Average)       0.2025 mg/m3 8 hours         ACGIH TLV (Threshold Limit Value)       TWA (Time Weighted Average)       2 mg/m3 (Respirable Fraction) 8 hours         NIOSH REL(Recommended Exposure       TWA (Time Weighted Average)       2 mg/m3 (Respirable Fraction) 10 hours         Limit)       TWA (Time Weighted Average)       2 mg/m3 (Respirable Fraction) 8 hours         SIOSH REL (Recommende Exposure       TWA (Time Weighted	USA OSHA	(OEL) Table Z-1, TWA	15 mg/m3	
USA OSHAUSA OSHA TWA (OEL Table Z-3)80 mg/m3 3/%SiO2USA NIOSHUSA NIOSH TWA (REL)6 mg/m3Amorphous Silica(112926-00-8)USA OSHAUSA OSHA6 mg/m3USA OSHAUSA OSHA TWA (Tabla Z-3)20 Million particals per cubic foot.USA NIOSHUSA NIOSHG mg/m36 mg/m3Carbon Black(1333-86-4)ACGIH TLV (Threshold Limit Value)TWA (Time Weighted Average)3 mg/m3 8 hoursOSHA PEL (Permissible Exposure Limit)TWA (Time Weighted Average)3.5 mg/m3 8 hoursNIOSH REL (Recommended ExposureTWA (Time Weighted Average)0.1mg of PAHs/cm3 10 hoursLimit)TWA (Time Weighted Average)0.1g of PAHs/cm3 10 hoursLimit)TWA (Time Weighted Average)0.025 mg/m3 8 hoursNIOSH REL (Recommended ExposureTWA (Time Weighted Average)0.025 mg/m3 8 hoursLimit)TWA (Time Weighted Average)0.025 mg/m3 8 hoursHydrated magnesium silicate(14807-96-6)TWA (Time Weighted Average)2 mg/m3 (Respirable Fraction) 8 hoursNIOSH REL(Recommended ExposureTWA (Time Weighted Average)2 mg/m3 (Respirable Fraction) 10 hoursNIOSH REL(Recommended ExposureTWA (Time Weighted Average)2 mg/m3 (Respirable Fraction) 10 hoursNIOSH REL (Permissible Exposure Limit)TWA (Time Weighted Average)15 mg/m3 (Total Dust) 8 hoursNIOSH REL (Permissible Exposure Limit)TWA (Time Weighted Average)15 mg/m3 (Total Dust) 8 hoursOSHA PEL (Permissible Exposure Limit)TWA (Time Weighted Average)15 mg/m3 (Total Dust) 8 hoursNIOSH REL (Recommende ExposureT	USA ACGIH	(TLV) TWA	1 mg/m3	
USA NIOSHUSA NIOSH TWA (REL)6 mg/m3Amorphous Silica(112926-00-8)USA OSHAUSA OSHAMorphous Silica(112926-00-8)USA OSHAUSA OSHAUSA OSHA TWA (Table Z-1)6 mg/m3USA OSHAUSA OSHAUSA NIOSH TWA (REL)6 mg/m3Carbon Black(1333-86-4)ACGIH TLV (Threshold Limit Value)TWA (Time Weighted Average)3 mg/m3 8 hoursOSHA PEL (Permissible Exposure Limit)TWA (Time Weighted Average)3.5 mg/m3 8 hoursNIOSH REL (Recommended Exposure Limit)TWA (Time Weighted Average)0.1mg of PAHs/cm3 10 hoursNIOSH REL (Recommended Exposure Limit)TWA (Time Weighted Average)0.205 mg/m3 8 hoursNIOSH REL (Recommended Exposure Limit)TWA (Time Weighted Average)0.202 mg/m3 8 hoursNIOSH REL (Recommended Exposure Limit)TWA (Time Weighted Average)0.202 mg/m3 8 hoursNIOSH REL (Recommended Exposure Limit)TWA (Time Weighted Average)0.202 mg/m3 8 hoursNIOSH REL(Recommended Exposure Limit)TWA (Time Weighted Average)2 mg/m3 (Respirable Fraction) 8 hoursNIOSH REL(Recommended Exposure Limit)TWA (Time Weighted Average)2 mg/m3 (Respirable Fraction) 10 hoursNIOSH REL (Recommende Exposure Limit)TWA (Time Weighted Average)15 mg/m3 (Total Dust) 8 hoursOSHA PEL (Permissible Exposure Limit)TWA (Time Weighted Average)15 mg/m3 (Respirable Fraction) 8 hoursNIOSH REL (Recommende Exposure Limit)TWA (Time Weighted Average)15 mg/m3 (Respirable Fraction) 8 hoursNIOSH REL (Recommende Exposure Limit)TWA (Time Wei	Amorphous Pyrogenic Silica(112945-52-5	5)		
Amorphous Silica(112926-00-8)       USA OSHA TWA (Table Z-1)       6 mg/m3         USA OSHA       USA OSHA TWA (Table Z-3)       20 Million particals per cubic foot.         USA NIOSH       USA OSHA TWA (Tabla Z-3)       20 Million particals per cubic foot.         USA NIOSH       USA NIOSH TWA (REL)       6 mg/m3         Carbon Black(1333-86-4)       TWA (Time Weighted Average)       3 mg/m3 & hours         ACGIH TLV (Threshold Limit Value)       TWA (Time Weighted Average)       3.5 mg/m3 & hours         NIOSH REL (Recommended Exposure       TWA (Time Weighted Average)       0.1mg of PAHs/cm3 10 hours         Limit)       TWA (Time Weighted Average)       0.1mg of PAHs/cm3 10 hours         Virostalline Silica(14808-60-7)       ACGIH TLV (Threshold Limit Value)       TWA (Time Weighted Average)       0.025 mg/m3 & hours         ACGIH TLV (Threshold Limit Value)       TWA (Time Weighted Average)       2 mg/m3 (Respirable Fraction) 8 hours         NIOSH REL(Recommended Exposure       TWA (Time Weighted Average)       2 mg/m3 (Respirable Fraction) 10 hours         Limestone(1317-65-3)       TWA (Time Weighted Average)       15 mg/m3 (Total Dust) & hours         OSHA PEL (Permissible Exposure Limit)       TWA (Time Weighted Average)       15 mg/m3 (Total Dust) & hours         NIOSH REL (Recommende Exposure       TWA (Time Weighted Average)       15 mg/m3 (Total Dust) & hours <t< td=""><td>USA OSHA</td><td>USA OSHA TWA (OEL Table Z-3)</td><td>80 mg/m3 3/%SiO2</td></t<>	USA OSHA	USA OSHA TWA (OEL Table Z-3)	80 mg/m3 3/%SiO2	
USA OSHAUSA OSHA TWA (Table Z-1)6 mg/m3USA OSHAUSA OSHA TWA (Table Z-3)20 Million particals per cubic foot.USA NIOSHUSA NIOSH TWA (REL)6 mg/m3Carbon Black(1333-86-4)	USA NIOSH	USA NIOSH TWA (REL)	6 mg/m3	
USA OSHAUSA OSHA TWA (Tabla Z-3)20 Million particals per cubic foot.USA NIOSHUSA NIOSH TWA (REL)6 mg/m3Carbon Black(1333-86-4)	Amorphous Silica(112926-00-8)			
USA NIOSHUSA NIOSH TWA (REL)6 mg/m3Carbon Black(1333-86-4)TWA (Time Weighted Average)3 mg/m3 & hoursACGIH TLV (Threshold Limit Value)TWA (Time Weighted Average)3.5 mg/m3 & hoursOSHA PEL (Permissible Exposure Limit)TWA (Time Weighted Average)3.5 mg/m3 & hoursNIOSH REL (Recommended ExposureTWA (Time Weighted Average)0.1mg of PAHs/cm3 10 hoursLimit)TWA (Time Weighted Average)0.1mg of PAHs/cm3 10 hoursLimit )TWA (Time Weighted Average)0.025 mg/m3 & hoursACGIH TLV (Threshold Limit Value)TWA (Time Weighted Average)0.025 mg/m3 & hoursHydrated magnesium silicate(14807-96-6)TWA (Time Weighted Average)2 mg/m3 (Respirable Fraction) 8 hoursACGIH TLV (Threshold Limit Value)TWA (Time Weighted Average)2 mg/m3 (Respirable Fraction) 10 hoursLimestone(1317-65-3)TWA (Time Weighted Average)2 mg/m3 (Respirable Fraction) 10 hoursOSHA PEL (Permissible Exposure Limit)TWA (Time Weighted Average)15 mg/m3 (Total Dust) 8 hoursOSHA PEL (Permissible Exposure Limit)TWA (Time Weighted Average)5 mg/m3 (Respirable Fraction) 8 hoursOSHA PEL (Recommende ExposureTWA (Time Weighted Average)15 mg/m3 (Total Dust) 8 hoursOSHA PEL (Recommende ExposureTWA (Time Weighted Average)5 mg/m3 (Respirable Fraction) 8 hoursOSHA PEL (Recommende ExposureTWA (Time Weighted Average)5 mg/m3 (Respirable Fraction) 8 hoursNIOSH REL (Recommende ExposureTWA (Time Weighted Average)5 mg/m3 (Respirable Fraction) 8 hoursNIOSH REL (Recommende ExposureT	USA OSHA	USA OSHA TWA (Table Z-1)	6 mg/m3	
USA NIOSHUSA NIOSH TWA (REL)6 mg/m3Carbon Black(1333-86-4)	USA OSHA	USA OSHA TWA (Tabla Z-3)	20 Million particals per cubic foot.	
ACGIH TLV (Threshold Limit Value)TWA (Time Weighted Average)3 mg/m3 8 hoursOSHA PEL (Permissible Exposure Limit)TWA (Time Weighted Average)3.5 mg/m3 8 hoursNIOSH REL (Recommended Exposure Limit)TWA (Time Weighted Average)3.5 mg/m3 8 hoursNIOSH REL (Recommended Exposure Limit)TWA (Time Weighted Average)0.1mg of PAHs/cm3 10 hoursCrystalline Silica(14808-60-7)TWA (Time Weighted Average)0.025 mg/m3 8 hoursACGIH TLV (Threshold Limit Value)TWA (Time Weighted Average)0.025 mg/m3 8 hoursHydrated magnesium silicate(14807-96-6)TWA (Time Weighted Average)2 mg/m3 (Respirable Fraction) 8 hoursNIOSH REL(Recommended Exposure Limit)TWA (Time Weighted Average)2 mg/m3 (Respirable Fraction) 10 hoursNIOSH REL(Recommended Exposure Limit)TWA (Time Weighted Average)2 mg/m3 (Respirable Fraction) 10 hoursNIOSH REL (Permissible Exposure Limit)TWA (Time Weighted Average)15 mg/m3 (Total Dust) 8 hoursOSHA PEL (Permissible Exposure Limit)TWA (Time Weighted Average)5 mg/m3 (Respirable Fraction) 10 hoursNIOSH REL (Recommende Exposure Limit)TWA (Time Weighted Average)15 mg/m3 (Total Dust) 8 hoursNIOSH REL (Recommende Exposure Limit)TWA (Time Weighted Average)5 mg/m3 (Respirable Fraction) 8 hoursNIOSH REL (Recommende Exposure Limit)TWA (Time Weighted Average)5 mg/m3 (Respirable Fraction) 8 hoursNIOSH REL (Recommende Exposure Limit)TWA (Time Weighted Average)5 mg/m3 (Respirable Fraction) 8 hoursNIOSH REL (Recommende Exposure Limit)<	USA NIOSH		6 mg/m3	
OSHA PEL (Permissible Exposure Limit)TWA (Time Weighted Average)3.5 mg/m3 8 hoursNIOSH REL (Recommended Exposure Limit)TWA (Time Weighted Average)3.5 mg/m3 8 hoursNIOSH REL (Recommended Exposure Limit)TWA (Time Weighted Average)0.1mg of PAHs/cm3 10 hoursCrystalline Silica(14808-60-7)TWA (Time Weighted Average)0.025 mg/m3 8 hoursACGIH TLV (Threshold Limit Value)TWA (Time Weighted Average)0.025 mg/m3 8 hoursHydrated magnesium silicate(14807-96-6)TWA (Time Weighted Average)2 mg/m3 (Respirable Fraction) 8 hoursACGIH TLV (Threshold Limit Value)TWA (Time Weighted Average)2 mg/m3 (Respirable Fraction) 10 hoursNIOSH REL(Recommended Exposure Limit)TWA (Time Weighted Average)2 mg/m3 (Respirable Fraction) 10 hoursNIOSH REL(Permissible Exposure Limit)TWA (Time Weighted Average)15 mg/m3 (Total Dust) 8 hoursOSHA PEL (Permissible Exposure Limit)TWA (Time Weighted Average)15 mg/m3 (Total Dust) 8 hoursNIOSH REL (Recommende Exposure Limit)TWA (Time Weighted Average)15 mg/m3 (Total Dust) 8 hoursNIOSH REL (Recommende Exposure Limit)TWA (Time Weighted Average)15 mg/m3 (Respirable Fraction) 8 hoursNIOSH REL (Recommende Exposure Limit)TWA (Time Weighted Average)5 mg/m3 (Respirable Fraction) 8 hoursNIOSH REL (Recommende Exposure Limit)TWA (Time Weighted Average)15 mg/m3 (Respirable Fraction) 8 hoursNIOSH REL (Recommende Exposure Limit)TWA (Time Weighted Average)10 mg/m3 8 hours	Carbon Black(1333-86-4)			
NIOSH REL (Recommended Exposure Limit)TWA (Time Weighted Average)3.5 mg/m3 8 hoursNIOSH REL (Recommended Exposure Limit)TWA (Time Weighted Average)0.1mg of PAHs/cm3 10 hoursOrystalline Silica(14808-60-7)TWA (Time Weighted Average)0.025 mg/m3 8 hoursACGIH TLV (Threshold Limit Value)TWA (Time Weighted Average)0.025 mg/m3 8 hoursHydrated magnesium silicate(14807-96-6)TWA (Time Weighted Average)2 mg/m3 (Respirable Fraction) 8 hoursNIOSH REL(Recommended Exposure Limit)TWA (Time Weighted Average)2 mg/m3 (Respirable Fraction) 10 hoursNIOSH REL(Recommended Exposure Limit)TWA (Time Weighted Average)2 mg/m3 (Respirable Fraction) 10 hoursNIOSH REL (Permissible Exposure Limit)TWA (Time Weighted Average)15 mg/m3 (Total Dust) 8 hoursOSHA PEL (Permissible Exposure Limit)TWA (Time Weighted Average)5 mg/m3 (Total Dust) 8 hoursNIOSH REL (Recommende Exposure Limit)TWA (Time Weighted Average)15 mg/m3 (Total Dust) 8 hoursNIOSH REL (Recommende Exposure Limit)TWA (Time Weighted Average)15 mg/m3 (Total Dust) 8 hoursNIOSH REL (Recommende Exposure Limit)TWA (Time Weighted Average)5 mg/m3 (Respirable Fraction) 8 hoursNIOSH REL (Recommende Exposure Limit)TWA (Time Weighted Average)15 mg/m3 (Respirable Fraction) 8 hoursNIOSH REL (Recommende Exposure Limit)TWA (Time Weighted Average)10 mg/m3 8 hours	ACGIH TLV (Threshold Limit Value)	TWA (Time Weighted Average)	3 mg/m3 8 hours	
Limit)TWA (Time Weighted Average)0.1mg of PAHs/cm3 10 hoursNIOSH REL (Recommended Exposure Limit)TWA (Time Weighted Average)0.025 mg/m3 8 hoursACGIH TLV (Threshold Limit Value)TWA (Time Weighted Average)0.025 mg/m3 8 hoursHydrated magnesium silicate(14807-96-6)TWA (Time Weighted Average)2 mg/m3 (Respirable Fraction) 8 hoursNIOSH REL(Recommended Exposure Limit)TWA (Time Weighted Average)2 mg/m3 (Respirable Fraction) 10 hoursLimestone(1317-65-3)TWA (Time Weighted Average)15 mg/m3 (Total Dust) 8 hoursOSHA PEL (Permissible Exposure Limit)TWA (Time Weighted Average)15 mg/m3 (Total Dust) 8 hoursNIOSH REL (Recommende Exposure Limit)TWA (Time Weighted Average)15 mg/m3 (Total Dust) 8 hoursOSHA PEL (Permissible Exposure Limit)TWA (Time Weighted Average)15 mg/m3 (Total Dust) 8 hoursNIOSH REL (Recommende Exposure Limit)TWA (Time Weighted Average)15 mg/m3 (Total Dust) 8 hourNIOSH REL (Recommende Exposure Limit)TWA (Time Weighted Average)5 mg/m3 (Respirable Fraction) 8 hoursNIOSH REL (Recommende Exposure Limit)TWA (Time Weighted Average)5 mg/m3 (Respirable Fraction) 8 hoursNIOSH REL (Recommende Exposure Limit)TWA (Time Weighted Average)5 mg/m3 (Respirable Fraction) 8 hoursNIOSH REL (Recommende Exposure Limit)TWA (Time Weighted Average)10 mg/m3 8 hours	OSHA PEL (Permissible Exposure Limit)	TWA (Time Weighted Average)	3.5 mg/m3 8 hours	
NIOSH REL (Recommended Exposure Limit)TWA (Time Weighted Average)0.1mg of PAHs/cm3 10 hoursCrystalline Silica(14808-60-7)ACGIH TLV (Threshold Limit Value)TWA (Time Weighted Average)0.025 mg/m3 8 hoursHydrated magnesium silicate(14807-96-5)ACGIH TLV (Threshold Limit Value)TWA (Time Weighted Average)2 mg/m3 (Respirable Fraction) 8 hoursNIOSH REL(Recommended Exposure Limit)TWA (Time Weighted Average)2 mg/m3 (Respirable Fraction) 10 hoursNIOSH REL(Recommended Exposure Limit)Not ApplicableNot ApplicableOSHA PEL (Permissible Exposure Limit)TWA (Time Weighted Average)15 mg/m3 (Total Dust) 8 hoursOSHA PEL (Permissible Exposure Limit)TWA (Time Weighted Average)5 mg/m3 (Total Dust) 8 hoursNIOSH REL (Recommende Exposure LImit)TWA (Time Weighted Average)5 mg/m3 (Total Dust) 8 hoursNIOSH REL (Recommende Exposure LImit)TWA (Time Weighted Average)5 mg/m3 (Respirable Fraction) 8 hoursNIOSH REL (Recommende Exposure LImit)TWA (Time Weighted Average)5 mg/m3 (Respirable Fraction) 8 hoursNIOSH REL (Recommende Exposure LImit)TWA (Time Weighted Average)5 mg/m3 (Respirable Fraction) 8 hoursNIOSH REL (Recommende Exposure LImit)TWA (Time Weighted Average)10 mg/m3 8 hoursTitanium Dioxide(13463-67-7)TWA (Time Weighted Average)10 mg/m3 8 hours		TWA (Time Weighted Average)	3.5 mg/m3 8 hours	
Limit )InterventionInterventionCrystalline Silica(14808-60-7)TWA (Time Weighted Average)0.025 mg/m3 8 hoursACGIH TLV (Threshold Limit Value)TWA (Time Weighted Average)2 mg/m3 (Respirable Fraction) 8 hoursHydrated magnesium silicate(14807-96-6)TWA (Time Weighted Average)2 mg/m3 (Respirable Fraction) 8 hoursACGIH TLV (Threshold Limit Value)TWA (Time Weighted Average)2 mg/m3 (Respirable Fraction) 10 hoursNIOSH REL(Recommended Exposure Limit)TWA (Time Weighted Average)2 mg/m3 (Respirable Fraction) 10 hoursLimestone(1317-65-3)Not ApplicableNot ApplicableOSHA PEL (Permissible Exposure Limit)TWA (Time Weighted Average)15 mg/m3 (Total Dust) 8 hoursOSHA PEL (Permissible Exposure Limit)TWA (Time Weighted Average)5 mg/m3 (Respirable Fraction) 8 hoursNIOSH REL (Recommende Exposure Limit)TWA (Time Weighted Average)15 mg/m3 (Total Dust) 8 hoursNIOSH REL (Recommende Exposure Limit)TWA (Time Weighted Average)5 mg/m3 (Respirable Fraction) 8 hoursNIOSH REL (Recommende Exposure Limit)TWA (Time Weighted Average)5 mg/m3 (Respirable Fraction) 8 hoursNIOSH REL (Recommende Exposure Limit)TWA (Time Weighted Average)5 mg/m3 (Respirable Fraction) 8 hoursNIOSH REL (Recommende Exposure Limit)TWA (Time Weighted Average)5 mg/m3 (Respirable Fraction) 8 hoursNIOSH REL (Recommende Exposure Limit)TWA (Time Weighted Average)10 mg/m3 8 hours				
Crystalline Silica(14808-60-7)TWA (Time Weighted Average)0.025 mg/m3 8 hoursACGIH TLV (Threshold Limit Value)TWA (Time Weighted Average)2 mg/m3 (Respirable Fraction) 8 hoursHydrated magnesium silicate(14807-96-6)TWA (Time Weighted Average)2 mg/m3 (Respirable Fraction) 8 hoursACGIH TLV (Threshold Limit Value)TWA (Time Weighted Average)2 mg/m3 (Respirable Fraction) 10 hoursNIOSH REL(Recommended Exposure Limit)TWA (Time Weighted Average)2 mg/m3 (Respirable Fraction) 10 hoursLimestone(1317-65-3)ACGIHNot ApplicableNot ApplicableOSHA PEL (Permissible Exposure Limit)TWA (Time Weighted Average)15 mg/m3 (Total Dust) 8 hoursOSHA PEL (Permissible Exposure Limit)TWA (Time Weighted Average)5 mg/m3 (Respirable Fraction) 8 hoursNIOSH REL (Recommende Exposure LImit)TWA (Time Weighted Average)15 mg/m3 (Total Dust) 8 hourNIOSH REL (Recommende Exposure LImit)TWA (Time Weighted Average)5 mg/m3 (Respirable Fraction) 8 hoursNIOSH REL (Recommende Exposure LImit)TWA (Time Weighted Average)5 mg/m3 (Respirable Fraction) 8 hoursTitanium Dioxide(13463-67-7)TWA (Time Weighted Average)5 mg/m3 (Respirable Fraction) 8 hoursACGIH TLV (Threshold Limit Value)TWA (Time Weighted Average)10 mg/m3 8 hours		TWA (Time Weighted Average)	0.1mg of PAHs/cm3 10 hours	
ACGIH TLV (Threshold Limit Value)TWA (Time Weighted Average)0.025 mg/m3 8 hoursHydrated magnesium silicate(14807-96-5)TWA (Time Weighted Average)2 mg/m3 (Respirable Fraction) 8 hoursACGIH TLV (Threshold Limit Value)TWA (Time Weighted Average)2 mg/m3 (Respirable Fraction) 10 hoursNIOSH REL(Recommended Exposure Limit)TWA (Time Weighted Average)2 mg/m3 (Respirable Fraction) 10 hoursLimestone(1317-65-3)Not ApplicableNot ApplicableOSHA PEL (Permissible Exposure Limit)TWA (Time Weighted Average)15 mg/m3 (Total Dust) 8 hoursOSHA PEL (Permissible Exposure Limit)TWA (Time Weighted Average)5 mg/m3 (Respirable Fraction) 8 hoursNIOSH REL (Recommende Exposure Limit)TWA (Time Weighted Average)15 mg/m3 (Total Dust) 8 hoursNIOSH REL (Recommende Exposure Limit)TWA (Time Weighted Average)5 mg/m3 (Respirable Fraction) 8 hoursNIOSH REL (Recommende Exposure Limit)TWA (Time Weighted Average)5 mg/m3 (Respirable Fraction) 8 hoursNIOSH REL (Recommende Exposure LImit)TWA (Time Weighted Average)5 mg/m3 (Respirable Fraction) 8 hoursNIOSH REL (Recommende Exposure LImit)TWA (Time Weighted Average)5 mg/m3 (Respirable Fraction) 8 hoursTitanium Dioxide(13463-67-7)TWA (Time Weighted Average)10 mg/m3 8 hours				
Hydrated magnesium silicate(14807-96-6)ACGIH TLV (Threshold Limit Value)TWA (Time Weighted Average)2 mg/m3 (Respirable Fraction) 8 hoursNIOSH REL(Recommended Exposure Limit)TWA (Time Weighted Average)2 mg/m3 (Respirable Fraction) 10 hoursLimestone(1317-65-3)Not ApplicableNot ApplicableOSHA PEL (Permissible Exposure Limit)TWA (Time Weighted Average)15 mg/m3 (Total Dust) 8 hoursOSHA PEL (Permissible Exposure Limit)TWA (Time Weighted Average)5 mg/m3 (Respirable Fraction) 8 hoursNIOSH REL (Recommende Exposure Limit)TWA (Time Weighted Average)5 mg/m3 (Total Dust) 8 hourNIOSH REL (Recommende Exposure Limit)TWA (Time Weighted Average)5 mg/m3 (Total Dust) 8 hourNIOSH REL (Recommende Exposure Limit)TWA (Time Weighted Average)5 mg/m3 (Respirable Fraction) 8 hoursNIOSH REL (Recommende Exposure Limit)TWA (Time Weighted Average)5 mg/m3 (Respirable Fraction) 8 hoursNIOSH REL (Recommende Exposure Limit)TWA (Time Weighted Average)5 mg/m3 (Respirable Fraction) 8 hoursNIOSH REL (Recommende Exposure LImit)TWA (Time Weighted Average)5 mg/m3 (Respirable Fraction) 8 hoursTitanium Dioxide(13463-67-7)TWA (Time Weighted Average)10 mg/m3 8 hours				
ACGIH TLV (Threshold Limit Value)TWA (Time Weighted Average)2 mg/m3 (Respirable Fraction) 8 hoursNIOSH REL(Recommended Exposure Limit)TWA (Time Weighted Average)2 mg/m3 (Respirable Fraction) 10 hoursLimestone(1317-65-3)			0.025 mg/m3 8 hours	
NIOSH REL(Recommended Exposure Limit)TWA (Time Weighted Average)2 mg/m3 (Respirable Fraction) 10 hoursLimestone(1317-65-3)ACGIHNot ApplicableNot ApplicableOSHA PEL (Permissible Exposure Limit)TWA (Time Weighted Average)15 mg/m3 (Total Dust) 8 hoursOSHA PEL (Permissible Exposure Limit)TWA (Time Weighted Average)5 mg/m3 (Respirable Fraction) 8 hoursNIOSH REL (Recommende Exposure Limit)TWA (Time Weighted Average)15 mg/m3 (Total Dust) 8 hoursNIOSH REL (Recommende Exposure Limit)TWA (Time Weighted Average)15 mg/m3 (Total Dust) 8 hourNIOSH REL (Recommende Exposure Limit)TWA (Time Weighted Average)5 mg/m3 (Respirable Fraction) 8 hoursNIOSH REL (Recommende Exposure LImit)TWA (Time Weighted Average)5 mg/m3 (Respirable Fraction) 8 hoursNIOSH REL (Recommende Exposure LImit)TWA (Time Weighted Average)5 mg/m3 (Respirable Fraction) 8 hoursTitanium Dioxide(13463-67-7)TWA (Time Weighted Average)10 mg/m3 8 hours				
Limit)hoursLimestone(1317-65-3)ACGIHNot ApplicableOSHA PEL (Permissible Exposure Limit)TWA (Time Weighted Average)15 mg/m3 (Total Dust) 8 hoursOSHA PEL (Permissible Exposure Limit)TWA (Time Weighted Average)5 mg/m3 (Respirable Fraction) 8 hoursNIOSH REL (Recommende Exposure Limit)TWA (Time Weighted Average)15 mg/m3 (Total Dust) 8 hourNIOSH REL (Recommende Exposure LImit)TWA (Time Weighted Average)15 mg/m3 (Total Dust) 8 hourNIOSH REL (Recommende Exposure LImit)TWA (Time Weighted Average)5 mg/m3 (Respirable Fraction) 8 hoursNIOSH REL (Recommende Exposure LImit)TWA (Time Weighted Average)5 mg/m3 (Respirable Fraction) 8 hoursTitanium Dioxide(13463-67-7)TWA (Time Weighted Average)10 mg/m3 8 hours	ACGIH TLV (Threshold Limit Value)	TWA (Time Weighted Average)	hours	
Limestone(1317-65-3)       Not Applicable       Not Applicable         ACGIH       Not Applicable       15 mg/m3 (Total Dust) 8 hours         OSHA PEL (Permissible Exposure Limit)       TWA (Time Weighted Average)       5 mg/m3 (Respirable Fraction) 8 hours         OSHA PEL (Permissible Exposure Limit)       TWA (Time Weighted Average)       5 mg/m3 (Respirable Fraction) 8 hours         NIOSH REL (Recommende Exposure       TWA (Time Weighted Average)       15 mg/m3 (Total Dust) 8 hour         LImit)       TWA (Time Weighted Average)       5 mg/m3 (Respirable Fraction) 8 hours         NIOSH REL (Recommende Exposure       TWA (Time Weighted Average)       5 mg/m3 (Respirable Fraction) 8 hours         NIOSH REL (Recommende Exposure       TWA (Time Weighted Average)       5 mg/m3 (Respirable Fraction) 8 hours         Titanium Dioxide(13463-67-7)       TWA (Time Weighted Average)       10 mg/m3 8 hours	NIOSH REL(Recommended Exposure	TWA (Time Weighted Average)	2 mg/m3 (Respirable Fraction) 10	
ACGIHNot ApplicableNot ApplicableOSHA PEL (Permissible Exposure Limit)TWA (Time Weighted Average)15 mg/m3 (Total Dust) 8 hoursOSHA PEL (Permissible Exposure Limit)TWA (Time Weighted Average)5 mg/m3 (Respirable Fraction) 8 hoursNIOSH REL (Recommende Exposure Limit)TWA (Time Weighted Average)15 mg/m3 (Total Dust) 8 hoursNIOSH REL (Recommende Exposure Limit)TWA (Time Weighted Average)5 mg/m3 (Respirable Fraction) 8 hoursNIOSH REL (Recommende Exposure Limit)TWA (Time Weighted Average)5 mg/m3 (Respirable Fraction) 8 hoursTitanium Dioxide(13463-67-7)TWA (Time Weighted Average)10 mg/m3 8 hours			hours	
OSHA PEL (Permissible Exposure Limit)       TWA (Time Weighted Average)       15 mg/m3 (Total Dust) 8 hours         OSHA PEL (Permissible Exposure Limit       TWA (Time Weighted Average)       5 mg/m3 (Respirable Fraction) 8 hours         NIOSH REL (Recommende Exposure Limit)       TWA (Time Weighted Average)       15 mg/m3 (Total Dust) 8 hours         NIOSH REL (Recommende Exposure Limit)       TWA (Time Weighted Average)       15 mg/m3 (Total Dust) 8 hour         NIOSH REL (Recommende Exposure Limit)       TWA (Time Weighted Average)       5 mg/m3 (Respirable Fraction) 8 hours         NIOSH REL (Recommende Exposure Limit)       TWA (Time Weighted Average)       5 mg/m3 (Respirable Fraction) 8 hours         Titanium Dioxide(13463-67-7)       TWA (Time Weighted Average)       10 mg/m3 8 hours				
OSHA PEL (Permissible Exposure Limit       TWA (Time Weighted Average)       5 mg/m3 (Respirable Fraction) 8 hours         NIOSH REL (Recommende Exposure Limit)       TWA (Time Weighted Average)       15 mg/m3 (Total Dust) 8 hour         NIOSH REL (Recommende Exposure Limit)       TWA (Time Weighted Average)       5 mg/m3 (Respirable Fraction) 8 hours         NIOSH REL (Recommende Exposure Limit)       TWA (Time Weighted Average)       5 mg/m3 (Respirable Fraction) 8 hours         Titanium Dioxide(13463-67-7)       TWA (Time Weighted Average)       10 mg/m3 8 hours				
NIOSH REL (Recommende Exposure LImit)       TWA (Time Weighted Average)       15 mg/m3 (Total Dust) 8 hour         NIOSH REL (Recommende Exposure LImit)       TWA (Time Weighted Average)       5 mg/m3 (Respirable Fraction) 8 hours         Titanium Dioxide(13463-67-7)       TWA (Time Weighted Average)       10 mg/m3 8 hours				
LImit)     TWA (Time Weighted Average)     5 mg/m3 (Respirable Fraction) 8 hours       NIOSH REL (Recommende Exposure LImit)     TWA (Time Weighted Average)     5 mg/m3 (Respirable Fraction) 8 hours       Titanium Dioxide(13463-67-7)     TWA (Time Weighted Average)     10 mg/m3 8 hours	OSHA PEL (Permissible Exposure Limit	TWA (Time Weighted Average)		
NIOSH REL (Recommende Exposure LImit)       TWA (Time Weighted Average)       5 mg/m3 (Respirable Fraction) 8 hours         Titanium Dioxide(13463-67-7)       TWA (Time Weighted Average)       10 mg/m3 8 hours		TWA (Time Weighted Average)	15 mg/m3 (Total Dust) 8 hour	
LImit)     hours       Titanium Dioxide(13463-67-7)     ACGIH TLV (Threshold Limit Value)       TWA (Time Weighted Average)     10 mg/m3 8 hours		TWA (Time Weighted Average)	5 mg/m3 (Respirable Fraction) 8	
ACGIH TLV (Threshold Limit Value) TWA (Time Weighted Average) 10 mg/m3 8 hours				
	Titanium Dioxide(13463-67-7)			
	ACGIH TLV (Threshold Limit Value)	TWA (Time Weighted Average)	10 mg/m3 8 hours	
	OSHA PEL (Permissible Exposure Limit)	TWA (Time Weighted Average)	15 mg/m3 8 hours	

### PERSONAL PROTECTIVE EQUIPMENT

**RESPIRATORY PROTECTION :** Wear approved dust mask.

HAND PROTECTION : Wear protective gloves.

**EYE PROTECTION :** Chemical goggles or safety glasses.

**SKIN AND BODY PROTECTION :** Wear suitable protective clothing.

**WORK HYGIENIC PRACTICES:** When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.



## 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	:	Solid
Melting point	:	55 - 90 deg C
Flash point	:	No data available.
Lower explosion limit	:	10 g/m <sup>3</sup>
Upper explosion limit	:	70 g/m <sup>3</sup>
Density	:	1.7185
Solubility	:	No data available.
Autoignition temperature	:	No data available.
Decomposition temperature	:	No data available.

## **10. STABILITY AND REACTIVITY**

**REACTIVITY :** This product is stable at normal handling and storage conditions.

**CHEMICAL STABILITY :** Stable under normal conditions.

**CONDITIONS TO AVOID :** Direct sunlight. Extremely high or low temperatures.

**INCOMPATIBLE MATERIALS :** Avoid contact with strong oxidizing agents.

HAZARDOUS DECOMPOSITION PRODUCTS: Fume. Carbon monoxide. Carbon dioxide.

## **11. TOXICOLOGICAL INFORMATION**

1,3,5-Triglycidyl Isocyanurate(2451-62-9)	
Acute toxicity - LD50 - oral - rat	100 - 200 mg/kg
Acute toxicity - LC50 - inhalation - rat -	> 650 mg/m3
male - 4 h	
Acute toxicity - LD50 - Dermal - rat- male	> 2000 mg/kg
& female	2000 mg/kg
Skin irritation - rabbit	Mild skin irritation - 24 hours
Eye irritation - rabbit	Severe eye irritation
Respiratory or skin sensation -	May cause sensitization by skin contact
Maximization test - guinea pig	
Germ cell mutagenicity	In vivo tests showed mutagenic effects
Germ cell mutagenicity - AMES test - S.	Positive
typhimurium	
Germ cell mutagenicity - AMES test -	Positive
mouse - male	
IARC	No component of this product present at levels greater than or equal to
	0.1% is identified as a probable, possible or confirmed human carcinogen
	by IARC
ACGIH	No component of this product present at levels greater than or equal to
	0.1% is identified as a carcinogen or potential carcinogen by ACGIH
NTP	No component of this product present at levels greater than or equal to
00114	0.1% is identified as a known or anticipated carcinogen by NTP
OSHA	No component of this product present at levels greater than or equal to
Denne ductive toxicity	0.1% is identified as a carcinogen or potential carcinogen by OSHA No data available
Reproductive toxicity	No data available
Specific target organ toxicity - single exposure	
Specific target organ toxicity - repeated	No data available
exposure	
Aspiration hazard	No data available
Additional information	To the best of our knowledge, the chemical, physical, and toxicological
	properties have not been thoroughly investigated
2-Mercaptobenzothiazole(149-30-4)	
Acute toxicity - LD50 - oral - male and	3800 mg/kg
femal rat	
Acute toxicity - LC50 - inhalation - rat	> 1270 mg/m3
Acute toxicity - LD50 - dermal - male and	> 7940 mg/kg
female rabbit	
Skin irritation - rabbit	No skin irritation / 24 h

CARDINAL SAFETY DATA SHEET

Eye irritation - rabbit	No eye irritation / 24 h
Respiratory or skin sensitisation - Buehler	May cause allergic skin reaction
test - guinea pig	
Respiratory or skin sensitisation - Maximisation test - guinea pig	May cause allergic skin reaction
Germ cell mutagenicity - Ames test - S. typhimurium	Negative
Germ cell mutagenicity - male and female mouse	Negative
IARC	No component of this product present at levels greater than or equal to
	0.1% is identified as a probable, possible or confirmed human carcinogen by IARC
ACGIH	No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH
NTP	No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen
OSHA	No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA
Reproductive toxicity	No data available
Specific target organ toxicity - single exposure	No data available
Specific target organ toxicity - repeated exposure	No data available
Aspiration hazard	No data available
Additional information	Repeated dose toxicity - male and female rat - lowest observed adverse effect level - 2500 mg/kg
Additional information	To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated
Aluminum Oxide(1344-28-1)	
Acute toxicity - LD50 - oral - rat	> 10,000 mg/kg
Acute toxicity - LC50 - inhalation - rat	> 2.6 mg/L / 4 h
Acute toxicity - dermal	No data available
Skin irritation - rabbit	No skin irritation
Eye irritation - rabbit	No eye irritation
Respiratory or skin sensitisation - maximisation test - guinea pig	DId not cause sensitisation on laboratory animals
Germ cell mutagenicity	No data available
Carcinogenicity	This product is or contains a component that is not classifiable as to its carcinogenicty based on its IARC, ACGIH, NTP, or EPA classification
IARC	No component of this product present at levels greater than or equal to 0.1% is identified as a probable, possible or confirmed human carcinogen by IARC
NTP	No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP
OSHA	No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA
Reproductive toxicity	No data available
Specific target organ toxicity - single exposure	No data available
Specific target organ toxicity - repeated exposure	No data available
Aspiration hazard	No data available
Additional information	Cough, chest pain, difficulty in breathing, gastrointestinal disturbance
Addittional information	Liver irregularities based on human evidence
Amorphous Pyrogenic Silica(112945-52-5)	
Acute toxicity - Inhalation	No data available
Acute toxicity - Dermal	No data available
Skin irritation	No data available
Respiratory or skin sensation	No data available
Germ cell mutagenicity - rat - lungs	Body fluid assay
Germ cell mutagenicity - rat	Unscheduled DNA synthesis
Carcinogenicity - Rat - Inhalation	Tumorigenic: Carcinogenic by RTECS criteria. Lungs, thorax, or respiration: tumors
IARC	Not classifiable as to its carcinogenicity to human
ACGIH	No component of this product present at levels greater than or equal to
	0.1% is identified as a carcinogen or potential carcinogen by ACGIH



NTP	No component of this product present at levels greater than or equal to
	0.1% is identified as as known or anticipated carcinogen
OSHA	No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA
Reproductive toxicity	No data available
Specific target organ toxicity - single	No data available
exposure	
Specific target organ toxicity - repeated	No data available
exposure	
Aspiration hazard	No data available
Additional information	To the best of our knowledge, the chemical, physical, and toxicological
Additional information	properties have not been thoroughly investigated Stomach irregularities based on human evidence
Amorphous Silica(112926-00-8)	
Acute toxicity	no data available
Acute toxicity: Inhalation	no data available
Acute toxicity: Dermal	no data available
Skin irritation	no data available
Eye irritation	no data available
Respiratory or skin sensation	no data available
Germ cell mutagenicity	no data available
Carcinogenicity: IARC: Group 3:	not classifiable as to its carcinogenicity to humans
ACGIH	no component of this product present at levels greater than or equal to
	0.1% is identified as a carcinogen or potential carcinogen by ACGIH
NTP	no component of this product present at levels greater than or equal to
	0.1% is identified as a known or anticipated carcinogen by NTP
OSHA	no component of this product present at levels greater than or equal to
<b>D</b>	0.1% is identified as a carcinogen or potential carcinogen by OSHA
Reproductive toxicity	no data available
Specific target organ toxicity - single exposure	no data available
Specific target organ toxicity - repeated	no data available
exposure	
Aspiration hazard	no data available
Additional information	Amorphous silica is not classified as to its carcinogenicity to humans, however, crystalline silica inhaled in the form of quartz or cristobalite from occupational sources is carcinogenic to humans (Group 1, IARC). Therefore, amorphous silica should be handled as if possessing the same hazards as the crystalline form. To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly
	investigated.
Additional information	Stomach - irregularities - based on human evidence
Barium Sulfate(7727-43-7)	
Acute toxicity - inhalation	No data available No data available
Acute toxicity - Dermal Skin irritation	No data available
Eye irritation	No data available
Respiratory or skin sensation	No data available
Germ cell mutagenicity - mouse - micronucleus test	No reported data
Carcinogenicity - rat - intrapleural -	Equivocal tumorigenic agent by RTECS criteria. Lungs, Thorax, or
tumorigenic	Respiration: Tumors
IARC	No component of this product present at levels greater than or equal to 0.1% is identified as a probable, possible, or confirmed human carcinogen by IARC
ACGIH	No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH
NTP	No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP
OSHA	No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA
Reproductive toxicity	No data available
Specific target organ toxicity - single	No data available
exposure	
	No data available



Additional information	Prolonged inhalation of dust may cause baritosis, a benign
	pneumoconiosis. If ingested, the presence of soluble barium salts as
	impurities may cause toxic reactions due to bioaccumulation., Damage to
	the lungs., To the best of our knowledge, the chemical, physical, and
	toxicological properties have not been thoroughly investigated.
Additional information	Stomach irregularities - based on human evidence
Carbon Black(1333-86-4)	
LD50 Oral - Rat	> 8,000 mg/kg, male and female, (OECD Test Guideline 401)
LD50 Inhalation - Rat	No data available
LD50 Dermal - Rabbit	> 3,000 mg/kg
Skin corrosion/irritation	No skin irritation - 24 h, (OECD Test Guideline 404)
Eye damage/irritation - Rabbit	No eye irritation, (OECD Test Guideline 405)
Respiratory/skin sensitization - Guinea pig	Did not cause sensitization on laboratory animals, (OECD Test Guideline
Respiratory/skin sensitization - Guinea pig	406)
Germ cell mutagenicity	Ames test, S. typhimurium, negative
Hamster - Ovary	Negative
DNA repair - Rat - Female	Negative
Carcinogenicity - Rat - Inhalation	Tumorigenic: Carcinogenic by RTECS criteria. Lungs, Thorax, or
	Respiration: Tumors. This product is or contains a component that has
	been reported to be possibly carcinogenic based on its IARC, ACGIH, NTP,
	or EPA classification. Limited evidence of carcinogenicity in animal studies.
IARC	2B - Group 2B: Possibly carcinogenic to humans (carbon black)
NTP	No component of this product present at levels greater than or equal
	to0.1% is identified as a known or anticipated carcinogen by NTP
OSHA	No component of this product present at levels greater than 0.1% is
	identified as a carcinogen or potential carcinogen by OSHA
Reproductive toxicity	No data available
Organ toxicity	Specific target organ toxicity - single exposure: No data available
Organ toxicity	Specific target organ toxicity - repeated exposure: No data available
Aspiration hazard	No data available
Additional Information	RTECS: FF5800000 To the best of our knowledge, the chemical , physical,
	and toxicological properties have not been throughly investigated.
Crystalline Silica(14808-60-7)	
Acute Inhalation toxicity	no data available
Acute Dermal toxicity	no data available
Skin irritation	no data available
eye irritation	no data available
Respiratory or skin sensation	no data available
Germ cell mutagenicity	no data available
Carcinogenicity	Limited evidence of carcinogenicity in human studies
IARC	Group 1: Carcinogenic to humans (Quartz)
ACGIH	No component of this product present at levels greater than or equal to
	0.1% is identified as a carcinogen or potential carcinogen by ACGIH
NTP	Known to be human carcinogen (Quartz)
OSHA	No component of this product present at levels greater than or equal to
	0.1% is identified as a carcinogen or potential carcinogen by OSHA
Reproductive toxicity	no data available
Specific target organ toxicity - single	no data available
exposure	
Specific target organ toxicity - repeated	may cause damage to organs through prolonged or repeated exposure
exposure - inhalation	
Aspiration hazard	no data available
Additional information	Prolonged inhalation of crystalline silica may result in silicosis, a disabling
	pulmonary fibrosis characterized by fibrotic changes and miliary nodules
	in the lungs, a dry cough, shortness of breath, emphysema, decreased
	chest expansion, and increased susceptibility to tuberculosis. In advanced
	stage, loss of appetite, pleuric pain, and total incapacity to work.
	Advanced silicosis may result in death due to cardiac failure or destruction
	of lung tissue. Crystalline silica is classified as group 1 "known to be
	of lung tissue. Crystalline silica is classified as group 1 "known to be carcinogenic to humans" by IARC and "sufficient evidence" of
	of lung tissue. Crystalline silica is classified as group 1 "known to be carcinogenic to humans" by IARC and "sufficient evidence" of carcinogenicity by the NTP., The chronic health risks are associated with
	of lung tissue. Crystalline silica is classified as group 1 "known to be carcinogenic to humans" by IARC and "sufficient evidence" of carcinogenicity by the NTP., The chronic health risks are associated with respirable particles of 3-4 um over protracted periods of time. Currently,
	of lung tissue. Crystalline silica is classified as group 1 "known to be carcinogenic to humans" by IARC and "sufficient evidence" of carcinogenicity by the NTP., The chronic health risks are associated with respirable particles of 3-4 um over protracted periods of time. Currently, there is a limited understanding of the mechanisms of quartz toxicity,
	of lung tissue. Crystalline silica is classified as group 1 "known to be carcinogenic to humans" by IARC and "sufficient evidence" of carcinogenicity by the NTP., The chronic health risks are associated with respirable particles of 3-4 um over protracted periods of time. Currently, there is a limited understanding of the mechanisms of quartz toxicity, including its mechanisms for lung carcinogenicity. Additional studies are
	of lung tissue. Crystalline silica is classified as group 1 "known to be carcinogenic to humans" by IARC and "sufficient evidence" of carcinogenicity by the NTP., The chronic health risks are associated with respirable particles of 3-4 um over protracted periods of time. Currently, there is a limited understanding of the mechanisms of quartz toxicity, including its mechanisms for lung carcinogenicity. Additional studies are needed to determine whether the cell transforming activity of quartz is
Additional information	of lung tissue. Crystalline silica is classified as group 1 "known to be carcinogenic to humans" by IARC and "sufficient evidence" of carcinogenicity by the NTP., The chronic health risks are associated with respirable particles of 3-4 um over protracted periods of time. Currently, there is a limited understanding of the mechanisms of quartz toxicity, including its mechanisms for lung carcinogenicity. Additional studies are



Hydrated magnesium silicate(14807-96-6)	
Acute toxicity - inhalation	No data available
Acute toxicity - dermal	No data available
Skin irritation - human	Mild skin irritation 3 h
Eye irritation	No data available
Respiratory or skin sensitisation	No ata available
Germ cell mutagenicity	No data available
Carcinogenicity - rat - inhalation	Equivocal tumorigenic agent by RTECS criteria. Lungs, thorax, or
cureinogenicity rut initialation	respiration: Tumors
IARC	Group 3: Not classifiable as to its carcinogenicity to humans
NTP	No component of this product present at levels greater than or equal to
	0.1% is identified as a known or anticipated carcinogen by NTP
OSHA	No component of this product present at levels greater than or equal to
	0.1% is identified as a carcinogen or potential carcinogen by OSHA
Reproductive toxicity	No data available
Specific target organ toxicity - single	No data available
exposure	
Specific target organ toxicity - repeated	No data available
exposure	
Aspiration hazard	No data available
Additional information	To the best of our knowledge, the chemical, physical, and toxicological
	properties have not been thoroughly investigated
Additional information	Stomach irregularities based on human evidence
Limestone(1317-65-3)	
Draize test, rabbit, eye	750 ug/24H severe
Draize test, rabbit, skin	500 mg/24H moderate
Oral, rat: LD50	6450 mg/kg
ACGIH, IARC, NTP, CA Prop 65	Not listed
Epidemiology	No information available
Teratogenicity	No information available
Reproductive effects	No information available
Mutagenicity	No information available
Neurotoxicity	No information available
Pentaerythritol tetrakis(6683-19-8)	
Acute toxicity - LD50 - oral - male rat	> 5000 mg/kg
Acute toxicity - LC50 - inahalation - male	> 1.95 mg/l / 4h
and female rat	
Acute toxicity - LD50 - dermal - male and	> 3160 mg/kg
female rabbit	> 5100 mg/kg
Acute toxicity - LD50 - intraperitoneal - rat	> 1000 mg/kg
Skin corrosion - rabbit	No skin irritation - 24 h
Eye irritation - rabbit	No eye irritation
Respiratory or skin sesnsitization - guinea	Does not cause skin sensitization
piq	
Germ cell mutagenicity - Ames test - S.	Negative
typhimurium	
Mutagenicity - micronucleus test - male	Negative
and female hamster	- J
IARC carcinogenicity	No component of this product present at levels greater than or equal to
,	0.1% is identified as a probable, possible, or confirmed human carcinogen
	by IARC
ACGIH	No component of this product present at levels greater than or equal to
	0.1% is identified as a carcinogen or potential carcinogen by ACGIH
NTP	No component of this product present at levels greater than or equal to
	0.1% is identified as a known or anticipated carcinogen by NTP
OSHA	No component of this product present at levels greater than or equal to
	0.1% is identified as a carcinogen or potential carcinogen by OSHA
Reproductive toxicity	No data available
Specific target organ toxicity - single	No data available
exposure	
Specific target organ toxicity - repeated	No data available
exposure	
Aspiration hazard	No data available
Titanium Dioxide(13463-67-7)	
	> 10000  mg/kg
Acute toxicity - LD50 - oral - rat	> 10000 mg/kg No data available
	> 10000 mg/kg No data available > 10000 mg/kg



Skin irritation - human	Mild skin irritation - 3 h
Eye irritation - rabbit	No eye irritation
Respiration or skin sensitisation	Will not occur
Germ cell mutagenicity - hamster - ovary -	No results available
micronucleus test	
Germ cell mutagenicity - hamster - lungs	DNA inhibition
Germ cell mutagenicity - hamster - ovary -	No results available
sister chromatid exchange	
Germ cell mutagenicity - mouse -	No results available
micronucleus test	
IARC	No component of this product present at levels greater than or equal to
	0.1% is identified as a probable, possible or confirmed human carcinogen
NTD	by IARC No component of this product present at levels greater than or equal to
NTP	0.1% is identified as a known or anticipated carcinogen
OSHA	No component of this product present at levels greater than or equal to
	0.1% is identified as a carcinogen or potential carcinogen by OSHA
Reproductive toxicity	No data available
Specific target organ toxicity - single	No data available
exposure	
Specific target organ toxicity - repeated exposure	No data available
Aspiration hazard	No data available
Additional information	To the best of our knowledge, the chemical, physical, and toxicological
	properties have not been thoroughly investigated
Tris(2,4-ditert-butylphenyl) phosphite(31570	
LD50 - oral - male and female rat - Acute	> 6000 mg/kg
Toxicity	
LD50 - dermal - male and female rat	> 2000 mg/kg
Skin irritation - rabbit	No skin irritation / 24 h
Eye irritation- rabbit	No eye irritation / 30 s
Respiratory or skin sensitization - guinea pig	Does not cause skin sensitization
Germ cell mutagenicity -Ames test (micronucleus test) - male and femae hamster	Negative
Carcinogenicity - oral - male and female rat	No adverse effect has been observed in chronic toxicity tests
IARC	No component of this product present at levels greater than or equal to 0.1% is identified as a probable, possible, or confirmed human carcinogen by IARC
ACGIH	No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH
NTP	No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen
OSHA	No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carconogen by OSHA
Reproductive toxicity	Not data available
Developmental toxicity - oral - rabbit	No adverse effect has been observed in chronic toxicity tests
Specific target organ toxicity - single	No data available
exposure	
Specific target organ toxicity - repeated exposure	No data available
Additional information	Repeated dose toxicity - rat - male and female - oral - No observed adverse effect level - >/ 1000 mg/kg
Additional information	No adverse effect has been observed in chronic toxicity tests

# 12. ECOLOGICAL INFORMATION

1,3,5-Triglycidyl Isocyanurate(2451-62-9)	
Toxicity to fish - static test LC50 - danio	> 77 mg/l - 96 h
rerio (zebra fish)	
Toxicity to daphnia and other aquatic	> 100 mg/l - 24 h
invertebrates - Immobilization - EC50 -	
daphnia magna (water flea)	

CARDINAL SAFETY DATA SHEET

Toxicity to algae - growth inhibition - EC50	29 - 30 mg/l - 72 h
<ul> <li>Desmodesmus subspicatus</li> </ul>	
Toxicity to bacteria - Respiration inhibition	> 100 mg/l 3 h
- IC50 - Sludge Treatment	
Persistence and degradability -	0.5 - 1% - not biodegradable
biodegradability - aerobic - exposure time:	
44 d	
Bioaccumulative potential	No data available
Mobility in soil	No data available
PBT & vPvB	not available/not required
Other adverse effects	An environmental hazard cannot be excluded in the event of
	unprofessional handling or disposal. Harmful to aquatic life with long
	lasting effects
2-Mercaptobenzothiazole(149-30-4)	
Toxicity to fish - flow-through test - LC50 -	0.73 mg/L / 96 h
rainbow trout	
Toxicity to daphnia and other aquatic	0.71 mg/L / 48 h
invertebrates - immobilization EC50 -	
Daphnia magna (water flea)	
Toxicity to algae - growth inhibition - EC50	0.5 mg/L - 72 h
- green algae	
Persistence and degradability -	1% - not readily biodegradable - exposure time: 28 d
biodegradability - biotic/aerobic	
Bioaccumulative potential -	0.1 mg/L / 42 d
bioaccumulation - carp	
Bioaccumulative potential -	< 0.8
Bioconcentration factor	
Mobility in soil	No data available
PBT and vPvB	Not available/not required
Other adverse effects	An environmental hazard cannot be excluded in the event of
	unprofessional handling or disposal. Very toxic to aquatic life with long
	lasting effects.
Aluminum Oxide(1344-28-1)	
Toxicity	No toxicity at the limit of solubility
Persisitence and degradability	The methods for determining biodegradability are not applicable to
	inorganic substances
Bioaccumulative potential	Does not bioaccumulate
Mobility in soil	No data available
PBT and vPvB	Not available/not required
Other adverse effects	No data available.
Amorphous Pyrogenic Silica(112945-52-5)	·
Toxicity	No data available
Persistence and degradability	No data available
Bioaccumulative potential	No data available
Mobility in soil	No data available
PBT and vPvB	not available/not required
Amorphous Silica(112926-00-8)	
Toxicity	no data available
Persistence and degradability	no data available
Bioaccumulative potential	no data available
Mobility in soil	no data available
PBT and vPvB	not available/not required
Barium Sulfate(7727-43-7)	
Toxicity	No data available
Persistence and degradability	The methods for determining biodegradability are not applicable in
reisistence and degradability	inorganic substances
Bioaccumulative potential	No data available
Mobility in soil	No data available
PBT and vPvB	
Carbon Black(1333-86-4)	not available/not required
Toyloity to fish I CEO	Dania raria (zahra fich) $> 1000 \text{ mg/l} = 06 \text{ h}$
Toxicity to fish LC50	Danio rerio (zebra fish) >1000 mg/l - 96 h
EC50 Toxicity to daphnia and other aquatic	Daphnia magna (Water flea) > 5600 mg/l - 24 h (OECD Test Guideline
EC50 Toxicity to daphnia and other aquatic invertebrates	Daphnia magna (Water flea) > 5600 mg/l - 24 h (OECD Test Guideline 202)
EC50 Toxicity to daphnia and other aquatic	Daphnia magna (Water flea) > 5600 mg/l - 24 h (OECD Test Guideline 202) Desmodesmus subspicatus (green algae > 10,000 mg/l - 72 h (OECD Test
EC50 Toxicity to daphnia and other aquatic invertebrates EC50 Toxicity to algae	Daphnia magna (Water flea) > 5600 mg/l - 24 h (OECD Test Guideline 202) Desmodesmus subspicatus (green algae > 10,000 mg/l - 72 h (OECD Test Guideline 201)
EC50 Toxicity to daphnia and other aquatic invertebrates	Daphnia magna (Water flea) > 5600 mg/l - 24 h (OECD Test Guideline 202) Desmodesmus subspicatus (green algae > 10,000 mg/l - 72 h (OECD Test





Mobility in soil	No data available
PBT and vPvB assessment	Not available/not required
Crystalline Silica(14808-60-7)	
Toxicity	no data available
Persistence and degradability	no data available
Bioaccumulative potential	no data available
Mobility in soil	no data available
PBT and vPvB	not available/not required
Hydrated magnesium silicate(14807-96-6)	
Toxicity	No data available
Persistence and degradability	No data available
Bioaccumulative potential Mobility in soil	No data available No data available
PBT and vPvB	Not available/not required
Limestone(1317-65-3)	
Ecotoxicity	No data available
Environmental	No information reported
Physical	No information available
Pentaerythritol tetrakis(6683-19-8)	
Toxicity to fish - static LC50 - zebra fish	> 100 mg/L / 96 h
Toxicity to daphnia and other aquatic	> 86 mg/L / 24 h
invertebrates - immobilization EC50 -	
daphnia magna (water flea)	
Toxicity to algae - static EC50 -	> 100 mg/L / 72 h
Scenedesmus subspicatus	
Toxicity to bacteria - respiration inhibition IC50 - sludge treatment	> 100 mg/L / 3 h
Persistence and degradability -	5% - not biodegradable : exposure time - 28 d
biodegradability - aerobic	
Bioaccumulative potential	No data available
Mobility in soil	No data available
PBT and vPvB	Not available/not required
Other adverse effects	No data available
Titanium Dioxide(13463-67-7)	
Toxicity to fish - LC50 - other fish	> 1000 mg/L / 96 h
Toxicity to daphnia and other aquatic	> 1000 mg/L / 48 h
invertebrates - EC50 - Dapphnia magna	
(water flea) Toxicity to daphnia and other aquatic	1000  mg/l / 48  h
invertebrates - ECO - Daphnia magna	1000 mg/L / 48 h
(water flea)	
Persistence and degradability	No data available
Bioaccumulative potential	No data available
Mobility in soil	No data available
PBT and vPbV	Not available/not required
Other adverse effects	No data available
Tris(2,4-ditert-butylphenyl) phosphite(31570	)-04-4)
Toxicity to fish - static LC0 - zebra fish	100 mg/L / 96 h
Toxicity to daphnia and other aquatic	510 mg/L / 24 h
invertebrates - static EC50 - Daphnia	
magna	> 75 ma/l / 72 h
Toxicity to algae - static EC50 -	> 75 mg/L / 72 h
Scenedesmus subspicatus	> 100 mg/L / 3 h
Toxicity to bacteria - respiration inhibition IC50 - sludge treatment	> 100 IIIg/L / 5 II
Persistence and degradability -	6% - not readily biodegradable - exposure: 28 d
biodegradability - aerobic	
Bioaccumulative potential	No data available
Mobility in soil	No data available
PBT and vPvB	not available/not required



## **13. DISPOSAL CONSIDERATIONS**

#### WASTE TREATMENT METHODS

#### **GENERAL INFORMATION :** No data available.

DISPOSAL METHOD: Dispose of in accordance with Local, State, Regional, National and International Regulations.

Ecology - waste materials: Avoid release to the environment.

## **14. TRANSPORT INFORMATION**

## \*CHECK WITH YOUR CARRIER FOR ADDITIONAL RESTRICTIONS THAT MAY APPLY.

USDOT GROUND DOT (DEPARTMENT OF TRANSPORTATION) PROPER SHIPPING NAME (DOT) : Not Regulated/Not Applicable HAZARDS CLASS : None UN/NA NUMBER : Not Applicable PACKING GROUP : None EMERGENCY RESPONSE GUIDE (ERG) : Not Applicable

IATA (AIR) DOT (INTERNATIONAL AIR TRANSPORTATION ASSOCIATION) PROPER SHIPPING NAME : Not Regulated/Not Applicable HAZARDS CLASS : Not Applicable UN/NA NUMBER : Not Applicable PACKING GROUP : Not Applicable EMERGENCY RESPONSE GUIDE (ERG) : Not Applicable

IMDG (OCEAN) PROPER SHIPPING NAME : Not Regulated , Not Applicable HAZARDS CLASS : Not Applicable UN/NA NUMBER : Not Applicable PACKING GROUP : Not Applicable EMERGENCY RESPONSE GUIDE (ERG) : Not Applicable

MARINE POLLUTANT : No SPECIAL PRECAUTIONS : P235 Keep cool.



**RDINAL** SAFETY DATA SHEET

## **15. REGULATORY INFORMATION**

US FEDERAL REGULATIONS All ingredients are TSCA (Toxic Substance Control Act) listed.

OSHA HAZARDS : Moderate skin irritant, Moderate eye irritant. EPCRA - Emergency CERCLA REPORTABLE QUANTITY

**SARA 304 Extremely Hazardous Substances Reportable Quantity :** This material does not contain any components with a section 304 EHS RQ.

## SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

SARA 311/312 Hazards : Acute Health Hazard, Chronic Health Hazard.

This product contains:	Chemical CAS#
Titanium Dioxide	13463-67-7
1,3,5-Triglycidyl Isocyanurate	2451-62-9
Hydrated magnesium silicate	14807-96-6
Aluminum Oxide	1344-28-1
Crystalline Silica	14808-60-7

SARA 313 : No SARA 313 chemicals are present

#### CLEAN AIR ACT :

#### INTERNATIONAL REGULATIONS

#### CLASSIFICATION ACCORDING TO REGULATION (EC) No. 1272/2008 (CLP) :

Eye Dam. 1	H318	Causes serious eye damage
Skin Sens. 1	H317	May cause an allergic skin reaction
Muta. 1B	H340	May cause genetic defects
Carc. 2	H351	Suspected of causing cancer
STOT RE 1	H372	Causes damage to organs through prolonged or repeated exposure
Aquatic Chronic 3	H412	Harmful to aquatic life with long lasting effects

## NATIONAL REGULATIONS

This product contains:	Chemical CAS#
~Titanium Dioxide	13463-67-7
^Crystalline Silica	14808-60-7

### National Regulations Key

~ Indicates a chemical listed by IARC as a possible carcinogen.

^ Indicates a chemical listed by IARC as carcinogenic to humans.



## STATE REGULATIONS **CALIFORNIA PROPOSITION 65**

This product contains:	Chemical CAS#
*Titanium Dioxide	13463-67-7
*Hydrated magnesium silicate	14807-96-6
*Crystalline Silica	14808-60-7
*Carbon Black	1333-86-4
*2-Mercaptobenzothiazole	149-30-4

## **Proposition 65 Key**

- WARNING: This product can expose you to a chemical(s), including those listed above, which is (are) known to the Λ State of California to cause cancer.
  - For more information visit <u>WWWPROP65.CA.GOV</u>.

WARNING: This product can expose you to a chemical(s), including those listed above, which is (are) known to the State of California to cause birth defects or other reproductive harm. For more information visit <u>WWWPROP65.CA.GOV</u>.

WARNING: This product can expose you to a chemical(s), including those listed above, which is (are) known to the State of California to cause cancer and birth defects or other reproductive harm. For more information visit <u>WWWPROP65.CA.GOV</u>.

## **Massachusetts Right to Know**

This product contains	Chemical CAS#	
Limestone	1317-65-3	
Titanium Dioxide	13463-67-7	
Barium Sulfate	7727-43-7	
Hydrated magnesium silicate	14807-96-6	
Aluminum Oxide	1344-28-1	
Crystalline Silica	14808-60-7	
Amorphous Silica	112926-00-8	
Carbon Black	1333-86-4	

## Pennsylvania Right to Know

This product contains	Chemical CAS#
Limestone	1317-65-3
Titanium Dioxide	13463-67-7
Barium Sulfate	7727-43-7
Hydrated magnesium silicate	14807-96-6
Aluminum Oxide	1344-28-1
Pentaerythritol tetrakis	6683-19-8
Crystalline Silica	14808-60-7
Amorphous Silica	112926-00-8
Carbon Black	1333-86-4
Tris(2,4-ditert-butylphenyl) phosphite	31570-04-4
Amorphous Pyrogenic Silica	112945-52-5
2-Mercaptobenzothiazole	149-30-4



## **New Jersey Right to Know**

This product contains	Chemical CAS#
Limestone	1317-65-3
Titanium Dioxide	13463-67-7
Barium Sulfate	7727-43-7
1,3,5-Triglycidyl Isocyanurate	2451-62-9
Hydrated magnesium silicate	14807-96-6
Aluminum Oxide	1344-28-1
Pentaerythritol tetrakis	6683-19-8
Crystalline Silica	14808-60-7
Amorphous Silica	112926-00-8
Carbon Black	1333-86-4
Tris(2,4-ditert-butylphenyl) phosphite	31570-04-4
Amorphous Pyrogenic Silica	112945-52-5
2-Mercaptobenzothiazole	149-30-4



**RDINAL** SAFETY DATA SHEET

## **16. OTHER INFORMATION**

## **Other Product Information:**

% Volatile by Volume :	0.00
% Solids by volume :	100.00


% Volatile by Weight : 0.00 % Solids by Weight : 100.00

## **VOC CONTENT:**

Content tested per EPA METHOD 24, ASTM D2369 is less than 1% Wt/Wt.

## HMIS RATING

Health :	2
Flammability :	1
Reactivity :	0
Personal Protection :	E



**MANUFACTURER DISCLAIMER :** The information contained in this Safety Data Sheet is considered to be true and accurate. Cardinal Paint and Powder makes no warranties, expressed or implied, as to the accuracy and adequacy of this information. This data is offered solely for the user's consideration, investigation and verification.